



Kanby LED Controller

COLOUR TEMPERATURE CHANGING LED CONTROLLER LUMINAIRES



SPECIFICATION

- Steel body, gear cover and end caps finished full polyester, non-yellowing white
- Ultra slim profile
- Polycarbonate controller
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit (CA versions)
- Fitted with 3000K and 6500K LEDs for colour temperature control

SmartScan Configurations



Find out more at www.thorlux.com/smartsan

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K to 6500K
RATED LIFE (HOURS)	59K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.9

LL/CW 119.9

For LED characteristics explanation see www.thorlux.com/led-guide

RANGE

COLOURACTIVE LUMINAIRE - with integral wireless SmartScan Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	LENGTH (mm)
1500	30W	KB 18813CA	4.1	1560
	37W	KB 18814CA	4.1	

COLOURCONTROL LUMINAIRE - for use with SmartScan Stand-alone Sensor

NOMINAL SIZE (mm)	LED	CAT. No.	APPROX. kg	LENGTH (mm)
1500	30W	KB 18816CC	4.1	1510
	37W	KB 18817CC	4.1	

EMERGENCY VERSION - prefix catalogue number with:

EKB - Emergency
TKB - AutoTest (Only available when selecting the 'CC' suffix)

WKB - SmartScan (Only available when selecting the 'CA' suffix)
 e.g. **WKB 18813CA** etc.

Add 0.3kg to weights listed



DIMENSIONS

