LEXI-65



With downlight


LEGEND KITS

ISO 7010 Self Adhesive Legend Kit - Cat. No. LXP 17613*



* Order separately from luminaire

DIMENSIONS



Thorlux Lighting Jul. 21



LEXI-65



With legend



LED EMERGENCY LUMINAIRES WITH DEDICATED SMARTSCAN WIRELESS TECHNOLOGY VERSIONS



SPECIFICATION

- Polycarbonate body finished white (RAL9016)
- Clear polycarbonate cover
- Extremely long LED lifetime, up to 100,000 hours
- 21.8m maximum viewing distance in accordance with BS EN 1838 when using legend kits
- Three hour, maintained emergency operation
- Simple to install, full status reporting SmartScan wireless communication versions
- Low power consumption (3.5W total)
- Integral downlight option for exit illumination
- Optional self-adhesive legend kit
- Status indicator shows operational condition
- Reliable Nickel Metal Hydride (NiMH) battery technology

At Platform 1 SmartScan emergency luminaires may self-test at any time. Consequently, caution should be exercised in situations where this may be inconvenient (such as hotel rooms or hospital wards). At Platform 2 specific testing times can be set via the SmartScan website (SmartScan Gateway required).

RANGE

LED	CAT. No.	DESCRIPTION	APPROX. kg	TYPE
SmartScan 2W 2W	WLX 17696 WLX 17697	Standard With integral downlight	1.0 1.0	Maintained ▲ Maintained ▲
AutoTest 2W 2W	TLX 17696 TLX 17697	Standard With integral downlight	1.0 1.0	Maintained ▲ Maintained ▲
Emergency 2W 2W	ELX 17696 ELX 17697	Standard With integral downlight	1.0 1.0	Maintained ▲ Maintained ▲

▲ Wire link may be removed to enable non-maintained operation

SPARES

DESCRIPTION	CAT. No.	APPROX. kg
Nickel Metal Hydride (NiMH) battery	EMB 848	0.15

End of life SmartScan batteries can be returned to Thorlux for recycling.



SmartScan Wireless Standards Compliance:

Europe: EN 300 220-1 V2.4.1 / EN 301 489-3 V1.6.1

Australasia: ACMA 2014 Radio Communication Standard 2014

Thorlux Patented Wireless Technology - GB2575724



* SmartScan versions only

