



ADDITIONAL COMPONENTS

FLEXIBLE LED STRIP

WATTAGE	LENGTH	3000K	4000K	APPROX. kg
1000 lumen versions				
7.1 W/m	5.0m	TOR 19764	-	0.098
6.6 W/m	5.0m	-	TOR 19766	0.098
2000 lumen versions				
14.9 W/m	5.0m	TOR 19765	-	0.098
13.8 W/m	5.0m	-	TOR 19767	0.098

EXTRUSIONS

DESCRIPTION	CAT. No.	APPROX. kg
Anodised aluminium extrusion 2.4m	TOR 18862	0.400
Opal polycarbonate diffuser 2.4m	TOR 18863	0.100
End cap (live end) x1	TOR 18864	0.003
End cap (dead end) x1	TOR 18865	0.003
Mounting clip x1	TOR 18866	0.002

MAXIMUM/MINIMUM TAPE RUN PER DRIVER

LED POWER (W/m)	LUMEN OUTPUT PER METRE LED STRIP EXPOSED	LED STRIP IN FIXTURE	DRIVER (W)	MINIMUM LENGTH PER DRIVER (mm)	MAXIMUM CONTINUOUS LENGTH PER DRIVER (mm)	MAXIMUM AMBIENT FOR USE WITHOUT ALUMINIUM EXTRUSION
7.1 - 6.6	1000	470	60	800 - 900	5000	35°C
14.9 - 13.8	2000	935	96 (100 DALI)	700	5000	25°C

CONNECTING LEADS

DESCRIPTION	CAT. No.	APPROX. kg
Starter lead - 300mm long	TOR 19768	0.004
Corner connection lead - 60mm long	TOR 19769	0.002
Corner connection lead - 150mm long	TOR 19770	0.002

DRIVERS

FOR USE WITH	WATTAGE	NON DIMMING	APPROX. kg	WATTAGE	DALI	APPROX. kg
7.1 W/m 6.6 W/m	60	TOR 18870	0.38	60	TOR 18873	0.180
14.9 W/m 13.8 W/m	96	TOR 18871	0.34	100	TOR 18874	0.254



LOW PROFILE LINEAR LED STRIP



SPECIFICATION

- Kit contains self-adhesive flexible LED strip, anodised aluminium extrusion, opal polycarbonate diffuser and driver to make up to 4.8m length
- Components can be selected separately to create bespoke solutions
- Anodised aluminum extrusion
- Opal polycarbonate diffuser
- LEDs "binned" to 3-step MacAdam ellipse providing excellent colour uniformity
- 3000K and 4000K versions

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K/4000K
RATED LIFE (HOURS)	50K - L70/B10
PROTECTION	-
DRIVER EFFICIENCY	>80%
REPLACEABLE	-
POWER FACTOR	>0.9

LL/CW **56.9**

For LED characteristics explanation see www.thorlux.com/led-guide

RANGE

LED	3000K Kit of parts	LED	4000K Kit of parts	APPROX. kg	CIRCUIT
1000 lumen versions					
7.1 W/m	TOR 19760	6.6 W/m	TOR 19762	1.5	L/A
2000 lumen versions					
14.9 W/m	TOR 19761	13.8 W/m	TOR 19763	1.5	L/A

CIRCUIT TYPE - suffix catalogue number with:

L - non-dimming (LED) / **A** - dimming (DALI) e.g. **TOR 19760L** etc.

KIT CONTAINS

DESCRIPTION

5.0m Flexible LED strip*	2 x Starter connector
2 x 2.4m Anodised aluminium extrusion	2 x End cap (live end)
2 x 2.4m Opal polycarbonate diffuser	2 x End cap (dead end)
1 x Driver	6 x Mounting clip

* Can be cut at 100mm intervals

DIMENSIONS



Remote gear unit - non-dimming version



Remote gear unit - DALI version

