

NEMO

Luminaire


Code LS Single Spot
Name Linescapes Spot Led

Measurerm.

Code 012019
Name Linescapes Spot Led

Luminaire Flux	369.00 lm	Luminaire Power	4.00 W	Efficacy	92.25 lm/W	Efficiency	92.25%
Lamps Flux	400.00 lm	Maximum value	4270.66 cd/klm	Position	C=120.00 G=1.00	CG	Asymmetrical
Round Luminaire		Diam.	35 mm	Height	75 mm		
Round Luminous Area		Diam.	30 mm	Height	0 mm		
Horizontal Luminous Area		0.000707 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000171 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		27-01-2000		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		400.00 lm	
Operator				Source Voltage [V]		230.00 V	
Temperature		25.00 °C		Source current [A]			
Humidity		60.00 %		Photocell			
Notes							

Line		Code Led	Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
			Name	Led	400.00	4.00	1
C.I.E.	89 100 100 92		D DIN 5040		A60		
F UTE	0.92 A		B NBN		BZ 1		



ULOR 0.00 %
DLOR 92.25 %
RN 0.00 %

