



WALL MOUNTED EMERGENCY LUMINAIRES WITH SMARTSCAN WIRELESS TECHNOLOGY



SPECIFICATION

- Steel body finished white (RAL9016)
- High performance optic with lateral light distribution
- Ideal for use in stairwell or corridor applications
- Three hour, non-maintained emergency operation
- Simple to install, full status reporting SmartScan wireless communication versions
- Low power consumption (2W total)
- Status indicator shows operational condition
- Reliable Nickel Metal Hydride (NiMH) battery technology

At Platform 1 SmartScan emergency luminaires may self-test at any time. Consequently, caution should be exercised in situations where this may be inconvenient (such as hotel rooms or hospital wards). At Platform 2 specific testing times can be set via the SmartScan website (SmartScan Gateway required).

SmartScan Configurations



Find out more at [www.thorlux.com/smartsan](http://www.thorlux.com/smartsan)

SmartScan Wireless Standards Compliance:

Europe: EN 300 220-1 V2.4.1 / EN 301 489-3 V1.6.1

Australasia: ACMA 2014 Radio Communication Standard 2014

Thorlux Patented Wireless Technology - GB2575724



\* SmartScan versions only

RANGE

LED POWER	CAT. No	APPROX. kg	TYPE
SmartScan 2W	<b>WCE 20079</b>	1.5	Non-maintained
AutoTest 2W	<b>TCE 20079</b>	1.5	Non-maintained
Emergency 2W	<b>ECE 20079</b>	1.5	Non-maintained

SPARES

DESCRIPTION	CAT. No.	APPROX. kg
Nickel Metal Hydride (NiMH) battery	<b>EMB 855</b>	0.28

DIMENSIONS

