


SKYCORE FAMILY



EMERGENCY TYPE ♦	PRODUCT CODE	WATTAGE	MOUNTING OPTIONS	SIZE	CONTROL TYPE	
W SmartScan*	SP SkyPro	16 16W	R Recessed	M 600 x 600	S SmartScan	
T AutoTest**		24 24W	S Surface		A Dimming (DALI)	
E Emergency**		30 30W	P Pendant		L Non-dimming	
		34 34W				

E.g. WSP16RMS

W SmartScan	SP SkyPro	16 16W	R Recessed	M 600 x 600	S SmartScan
--------------------	------------------	---------------	-------------------	--------------------	--------------------

♦ Optional, leave blank if emergency is not required

* **Only** available with **S** or **L** control type

** **Not** available with **S** control type

WEIGHTS

SIZE	APPROX. kg
Recessed	4.2
Surface/Suspended	8.4


EMERGENCY

Add 0.3kg to weight listed.

SMARTSCAN

Add 0.2kg to weight listed.

PHOTOMETRIC GUIDE



Luminaire Lumen Output
16W = 2705lm
24W = 3750lm
30W = 4745lm
34W = 5315lm*

* Exceeds EN12464-1 / LG7 3000 cd/m² limit

ACCESSORIES

DESCRIPTION	CAT. No.
Optional side arm suspension kit ▲	IK 20277
Recessing frame for plasterboard ceiling	RAD16877

▲ 4 arms per kit - not required for lay-in mounting

WEB LINK >
"PLUG AND PLAY"
LIGHTING CABLE
MANAGEMENT



LOW GLARE POLYCARBONATE DIFFUSER LUMAIRES



SPECIFICATION

- Steel body finished full polyester non-yellowing white (RAL9016)
- Shallow body depth of 59mm, 94mm including the gearbox
- Supplied with low glare polycarbonate TP(a) fire-retardant diffuser to aid EN12464-1 / LG7 (<3000cd/m² @ 65°) compliance
- Suitable for most ceiling types with optional side arm suspensions and plasterboard mounting kits
- Designed to exclude dust, dirt and flies. All control gear is outside the lamp enclosure
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit
- Rapid installation using Fast-Fix wiring enclosure or SmartScan plug and play TEE connectors
- Wattage selectable during installation. Please see photometric guide for options and lumen output
- Fitted with 4000K LEDs

SmartScan Configurations



Find out more at www.thorlux.com/smartsan

LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	100K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>87%
REPLACEABLE	YES
POWER FACTOR	>0.95

LL/CW 144.2

For LED characteristics explanation see www.thorlux.com/led-guide




Diffuser prisms



SmartScan version

DIMENSIONS





SKYPRO

Recessed


Surface

Pendant




MOUNTING ARRANGEMENTS

Exposed T bar




NOTE: - Side arm suspension kit to be ordered separately.

Spring Tee




NOTE: - Side arm suspension kit to be ordered separately.

Lay-in on
exposed
T bar



Plasterboard ceiling
with recessing frame



NOTE: - Plasterboard recessing frame to be ordered separately.