



## TAMPER, IMPACT AND LIGATURE-RESISTANT SURFACE LED LUMINAIRES



### SPECIFICATION

- Robust and durable extruded aluminium body finished white (RAL 9010)
- Die-cast aluminium end caps finished white (RAL 9010)
- Clear prismatic polycarbonate lens
- Body dissipates heat, ensuring long control gear life in higher ambient temperatures
- Suitable for both individual and in-line mounting
- Complies with food production standards IFS, HACCP and BRC
- SmartScan Radar versions with sensor discretely hidden behind the cover
- Fitted with 4000K LEDs

### LED CHARACTERISTICS

CRI	80
COLOUR TEMPERATURE	4000K
RATED LIFE (HOURS)	50K - L70/B10
PROTECTION	-
DRIVER EFFICIENCY	>85%
REPLACEABLE	YES
POWER FACTOR	>0.95

**LL/CW 83.0**

For LED characteristics explanation see [www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

### RANGE

LENGTH (mm)	LED	CAT. No.	APPROX. kg	CIRCUIT
697	19W	<b>VT 17215</b>	5.0	L/A/R
1307	56W	<b>VT 17216</b>	9.0	L/A/R


CIRCUIT TYPE - suffix catalogue number with:

**L** - non-dimming (LED) / **A** - dimming (DALI) / **R** - SmartScan Radar e.g. **VT 17215L** etc. SmartScan Radar add 0.1kg to weights listed.


EMERGENCY VERSION (56W version only) - prefix catalogue number with:

**EVT** - Emergency (Not available when selecting the 'R' suffix)  
**WVT** - SmartScan (Not available when selecting the 'L' and 'A' suffixes)  
 e.g. **EVT 17216L** etc.  
 Add 0.3kg to weights listed.

### DIMENSIONS



### PHOTOMETRIC GUIDE



Luminaire Lumen Output  
 19W = 1635lm  
 56W = 5060lm

### SmartScan Radar Configurations



Find out more at [www.thorlux.com/smartsan](http://www.thorlux.com/smartsan)