

# PRODUCTS

## SKYPRO

COLOUR TEMPERATURE CHANGING  
LOW GLARE POLYCARBONATE  
DIFFUSER LUMINAIRES



### SPECIFICATION

- Steel body finished full polyester non-yellowing white (RAL9016)
- Shallow body depth
- Supplied with low glare polycarbonate TP(a) fire-retardant diffuser to aid EN12464-1 / LG7 (<3000cd/m<sup>2</sup>@65°) compliance
- Suitable for most ceiling types with optional side arm suspensions and plasterboard mounting kits
- Designed to exclude dust, dirt and flies. All control gear is outside the LED enclosure
- SmartScan wireless technology removes the need for control cabling. Ideal for retro-fit (CA versions)
- Rapid installation using Fast-Fix wiring enclosure or SmartScan plug and play TEE connectors
- Wattage selectable during installation. Please see photometric guide for options and lumen output
- Fitted with 3000K and 6500K LEDs for colour temperature control

### LED CHARACTERISTICS

CRI	80+
COLOUR TEMPERATURE	3000K to 6500K
RATED LIFE (HOURS)	100K - L80/B10
PROTECTION	LUX GUARD
DRIVER EFFICIENCY	>76%
REPLACEABLE	YES
POWER FACTOR	>0.9

LL/CW **119.4**

For LED characteristics explanation see [www.thorlux.com/led-guide](http://www.thorlux.com/led-guide)

### CONFIGURATOR

EMERGENCY TYPE	PRODUCT CODE	WATTAGE	MOUNTING OPTION	SIZE	CONTROL TYPE
W SmartScan*	SP Skypro	16 16W	R Recessed	M 600 x 600mm	CA ColourActive
T AutoTest**		22 22W			CC ColourControl
E Emergency**		28 28W			
		32 32W			

#### E.g. WSP16RMCA

W SmartScan	SP Skypro	16 16W	R Recessed	M 600 x 600mm	CA ColourActive
-------------	-----------	--------	------------	---------------	-----------------

◆ Optional, leave blank if emergency is not required

\* Prefix W only with CA control gear \*\* Prefix E and T only with CC control gear


### SmartScan Configurations



Find out more at [www.thorlux.com/smartsan](http://www.thorlux.com/smartsan)



### DIMENSIONS



### WEIGHTS

APPROX. kg

4.2

EMERGENCY  
Add 0.3kg to weight listed.

COLOURACTIVE  
Add 0.2kg to weight listed.

### ACCESSORIES

DESCRIPTION	CAT. NO.
Recessing frame for plasterboard ceiling	<b>RAD 16877</b>
Optional side arm suspension kit (4 arms per kit - not required for lay-in mounting)	<b>IK 20277</b>

WEB LINK >  
"PLUG AND PLAY"  
LIGHTING CABLE  
MANAGEMENT

