



WIRELESS USER CONTROL OF SMARTSCAN LUMINAIRES




SPECIFICATION

- Provides manual control or override of the colour temperature of ColourActive luminaires
- 12 buttons providing On (Eco), Off, 5 fixed dimming levels, 5 fixed colour temperature levels
- Mains (230V) or battery powered versions available
- Communicates wirelessly with ColourActive luminaires
- Mains versions have additional wireless connectivity allowing control from the SmartScan App (iOS and Android)
- Requires a 35mm deep single-gang pattress (mains version only)
- Battery version, supplied complete with batteries and self-adhesive fixings, can be mounted directly to any flat surface or wall
- Multiple SmartScan Colour touch plates can be used to provide multi-point control
- Programmable using the SmartScan Programmer

RANGE

DESCRIPTION	CAT. No.	APPROX. kg
SmartScan Colour - Battery powered	SS 20446	0.8
SmartScan Colour - Mains powered	SS 20447	0.8

DIMENSIONS



POWER OPTIONS



SmartScan Wireless Standards Compliance:

Europe: EN 300 220-1 V2.4.1 / EN 301 489-3 V1.6.1

Australasia: ACMA 2014 Radio Communication Standard 2014

Thorlux Patented Wireless Technology - GB2575724