


NEW



Design by
Ángel Díaz Cambrero



Ease of pictogram placement.

EXITALYA MAXI Recessed

(Recessed Wall Mounted & Ceiling Recessed Mounted)

SPECIFICATION

- Polycarbonate body
- IP IP42
- IK IK04
- Duration: 1 - 3 - 8 h · Battery: LiFePO₄
- Charging time: 12 h
- Supply: 230 V - 50 Hz
- LED LED temperature: 6000 °K
- Working temperature: 0 °C to +40 °C
- AutoTest
- SmartZ[®]

[VIEW EVO10 RANGE](#)

WARRANTY
5 YEAR

EVO10 WARRANTY
10 YEAR

STANDARDS COMPLIANCE

- EN-60598-2-22
- Pictographs: EN ISO7010
- AutoTest: EN-62034
- DALI-2: EN 62386
- Wireless SmartZ[®]: ETSI EN 303 447-1

DIMENSIONS (mm)

Ceiling Recessed Mounted

VIEWING DISTANCE

CERTIFICATIONS

New transparent frame

RANGE				
	Type*	Dur.	Battery	Part number
AutoTest	M	1 h	3.2V 1.0A/h LiFePO ₄	LYR5070LXP
	M	3 h	3.2V 1.5A/h LiFePO ₄	LYR5070LXP3
	M	1 h	3.2V 1.0A/h LiFePO ₄	LYR5070LAP
	M	3 h	3.2V 1.5A/h LiFePO ₄	LYR5070LAP3
Wireless SmartZ [®]	M	1 h	3.2V 1.0A/h LiFePO ₄	LYR5070LWP
	M	3 h	3.2V 1.5A/h LiFePO ₄	LYR5070LWP3
	M	8 h	3.2V 3.0A/h LiFePO ₄	LYR5070LWP8

*M: Maintained.

For version in black colour, add an 'N' at the end of the part number.



180° adaptable

Its specific design makes it an exign sign adaptable to any position on the surface where it is installed: ceiling, wall or sloping ceiling.

The banner is made of a very innovative self-diffusing material that provides a perfect and uniform diffusion of light.



Ease of pictogram placement

